




## Panda 24 NE PVK-U Specification



### Engine;

Type	Kubota – vertical 4-stroke diesel engine type V 1505
Cylinder	4
Bore / stroke	78 / 78.4 mm
Displacement	1498 cm <sup>3</sup>
Start system	Electric – 12v
Cooling system	Water-cooled

### Alternator ;

Type	Fischer Panda
Voltage	231v / 50Hz single phase
Polarity	2 – pole
Nominal Frequency	50 Hz +/- 1.5Hz
Nominal Voltage	230v +/- 3 volt
Nominal Output	21 kW / 24.7 kVA
Isolation Class	F
Protection Class	IP 54
Regulation	Voltage regulation by patented VCS system
Cooling	Water-cooled

**Dimensions of generator ;** L1190mm x W580mm x H670mm, Weight ; 450 kgs.

The complete generator is mounted inside a super-silent capsule type MPL – 4DS. Also fitted to the generator as standard is DC charging alternator, engine driven water cooling pump, 2 pole DC wiring and complete 1st and 2nd stage exhaust silencers.

Supplied with the generator would be remote AC control / booster box, fuel pump, connecting looms, full instruction manual, and remote control panel giving on/off, start/stop, pre-heat, digital hour meter and all warning indications. The warning indications work on an emergency shut down principle.

A cooling radiator system would also be supplied with the generator. The radiator will be fitted with a thermostatically controlled AC fan or fans. All our radiator systems are sized to work at ambients of up to + 50 degrees C.

This specification produces a very quiet, reliable generator that is well known in the more demanding commercial applications.