



Fischer Panda UK

GENERATORS – DESALINATION – AIR-CONDITIONING – POWER ELECTRONICS



AUTOTERM Air 2D

WITH HIGH ALTITUDE SENSOR &
SILENT FUEL PUMP

- Works on diesel fuel
- Maximum heating capacity of 2 kW for 12V or 24V model
- Produces up to 86 m³ of hot airflow hourly
- Used to heat small size space
- Reliable operation in low temperatures (up to -45°C/-49°F)
- Available in a standard or 3 different marine installation kits
- Low noise level, low fuel consumption (Max – 0,24 l/h), implemented self-diagnostic
- Can be operated with the control panel or via smartphone with an additional modem
- Best suited for small truck cabins, commercial vehicle cabins or cargo compartments, small campers, off-highway vehicles, boats (up to 33 feet/10 m long)

	High	Low
Voltage	12V or 24V	
Heating medium	Air	
Heating capacity	2.0 kW	0.8 kW
Hot air flow	86 m ³ /h	34 m ³ /h
Power consumption	29 W	10 W
Max. work altitude (MASL)	4200 m (High altitude control unit)	
Fuel	Diesel	
Fuel consumption	0.24 l/h	0.10 l/h
Control option	Control panel or Modem	
Weight of the heater	2.9 kg	

STANDARD INSTALLATION KIT: Air Heater AUTOTERM Air 2D

• fuel pump • fuel pump wire • power supply wire • exhaust pipe • air intake pipe with silencer • insulation for exhaust pipe • exhaust silencer with mounting kit • fuel standpipe • fuel pipe • mounting kit for harnesses • air intake mounting kit • mounting kit for fuel system • mounting kit for exhaust pipe and heater • control panel wire • warranty certificate • manual • duplicate label



17 Blackmoor Road, Ebblake Industrial Estate, Verwood, Dorset, BH31 6AX.

Tel: 01202 820840 Fax: 01202 828688 info@fischerpanda.co.uk www.fischerpanda.co.uk

Registered in England No: 2892031 VAT No. GB 631 7640 48 NATO CAGE No. KC 184 DUNS No. 578389165

