



Fischer Panda®

Power
wherever
you are™

SPECIFICATION SHEET - Panda PMS 12000x



Engine;

Type	Kubota – vertical 4-stroke diesel engine type D722
Cylinder	3
Bore / stroke	67 / 68 mm
Displacement	719 cm ³
Start system	Electric – 12v
Cooling system	Freshwater-cooled

Alternator;

Type	Fischer Panda
Voltage	230v / 50Hz single phase
Polarity	2 – pole
Nominal Frequency	50 Hz +/- 1.5Hz
Nominal Voltage	230v +/- 3 volt
Nominal Output	10 kW / 12.3 kVA
Insulation Class	H
Protection Class	IP 54
Regulation	Voltage regulation by patented VCS system
Cooling	Freshwater-cooled

Dimensions; L700mm x W470mm x H580mm, **Weight;** 192 kg.

The complete generator is mounted inside a super-silent capsule type GRP –3DS. Also fitted to the generator as standard is a 12v DC charging alternator, engine driven water cooling pump, 2 pole DC wiring, built in heat exchanger for the freshwater cooling of both the engine and alternator, VCS voltage control and oil cooled rear bearing.

Supplied with the generator would be remote AC control / booster box, fuel pump, connecting looms, full instruction manual, and new 'x' remote control panel giving on/off, start/stop, pre-heat, digital hour meter and all warning indications. The warning indications work on an emergency shut down principle.