



Fischer Panda®

Power
wherever
you are™

FISCHER PANDA – SPECIFICATION SHEET

Panda PMS 24x



Engine:

Type	Kubota – vertical 4-stroke diesel engine type V1505
Cylinder	4
Bore / stroke	78 / 78.4 mm
Displacement	1498 cm ³
Start system	Electric – 12v
Cooling system	Freshwater-cooled

Alternator:

Type	Fischer Panda
Voltage	230v / 50Hz / Single Phase
Polarity	2 – pole
Nominal Frequency	50 Hz +/- 1.5Hz
Nominal Voltage	230V +/- 3 Volt
Nominal Output	20.4 kW / 24 kVA
Isolation Class	F
Protection Class	IP 54
Regulation	Voltage regulation by patented VCS system
Cooling	Freshwater-cooled

Dimensions of Generator: L1010mm x W540mm x H674mm, Weight: 355 kg.

The complete generator is mounted inside a super-silent capsule type GRP –3DS. Also fitted to the generator as standard is a 12v DC charging alternator, engine driven water cooling pump, 2 pole DC wiring, built in heat exchanger for the freshwater cooling of both the engine and alternator, VCS voltage control and oil cooled rear bearing.

Supplied with the generator would be remote AC control / booster box, fuel pump, connecting looms, full instruction manual, and new remote x control panel giving on/off, start/stop, pre-heat, digital hour meter and all warning indications. The warning indications work on an emergency shut down principle.

Fischer Panda UK Ltd. 17 Blackmoor Road,
Ebblake Industrial Estate, Verwood. Dorset BH31 6AX
Tel: +44 (0)1202 820840 Fax: +44 (0)1202 828688
www.fischerpanda.co.uk